


# TECHNICAL DATA SHEET

<b>Name :</b>	<b>Nylon 70D/210T WR PU</b>		
<b>Supplier :</b>	KINETIC s.r.o. SNP 9/6 ; 796 07Držovice IČO:27728234 ; DIČ: CZ27728234 tel.: 582 365 770 email : kinetic@kinetic.cz		
<b>Manufactured :</b>	Taiwan		
<b>PROJECT</b>	TESTING RESULTS	TESTING STANDART	TOLERANCE
<b>Description</b>	Nylon 70D/210T WR PU		
<b>Textile :</b>	<u>100% nylon</u>		
<b>Lamination :</b>	Polyuretan		
<b>Weight :</b>	71,57	ISO 3801 (g/m <sup>2</sup> )	+/- 5%
<b>Dimensions :</b>	fabric width 58" - length 1 roll 50m		
<b>Tensile strength:</b>			
<b>warp</b>	683.95	ISO 13934-1N	+/- 5%
<b>weft</b>	388.89		+/- 5%
<b>Tear strength:</b>			
<b>warp</b>	20.40	ISO 13937-2 N	
<b>weft</b>	16.54		
<b>Abrasion resistance :</b>	250 000	ISO 12947-2 (Cycles)	
<b>Water column :</b>	1119	ATCC-127 (mmH <sub>2</sub> O)	
<b>Others</b>			
<b>Laundry symbols :</b>			
	DO NOT WASH	DO NOT BLEACH	DO NOT TUMBLE DRY
		DO NOT IRON	DO NOT DRY CLEAN
<b>Suitable method of treatment :</b>	Textile side of the fabric clean either dry with a soft brush or slightly wet cloth		
	The fabric should be left to dry at room temperature		
<b>Recommended</b>	Recommended to store in a horizontal position, in a dry and well-ventilated area, away from sunlight and UV radiation		
	In Drzovice 1.10.2024		