








**KINETIC s.r.o**  
**SNP 9/6**  
**796 07 Držovice**  
 ☎ +420 582 365 770    kinetic@kinetic.cz



## TECHNICAL DATA SHEET

<b>Name :</b>	<b>Nylon 70D/190T WR PVC REACH</b>		
<b>Supplier :</b>	KINETIC s.r.o. SNP 9/6 ; 796 07Držovice IČO:27728234 ; DIČ: CZ27728234 tel.: 582 365 770 email : kinetic@kinetic.cz		
<b>Manufactured :</b>	Taiwan		
<b>PROJECT</b>	<b>TESTING RESULTS</b>	<b>TESTING STANDART</b>	<b>TOLERANCE</b>
<b>Description</b>	Nylon 70D/190T WR PVC REACH		
<b>Dyeing method:</b>	Piece dyeing		
<b>Textile :</b>	<u>100% NYLON</u>		
<b>Lamination :</b>	REACH PVC		
<b>Weight :</b>	207,4 g/m2	ISO 3801 (g/m2)	+/- 5%
<b>Dimensions :</b>	fabric width 58" - length 1 roll 40m		+/- 5%
<b>Tensile strength:</b>	warp: 427.66 lbf	ISO 13934-1 (N)	+/- 5%
	weft: 268.11		+/- 5%
<b>Tear strength:</b>	weft: 16.10	ISO 13937-2 (N)	+/- 5%
	weft: 10.08		+/- 5%
<b>Water column :</b>	more than 20000	ATCC-127 (mmH2O)	+/- 5%
<b>Adhesion of coating to fabric:</b>	warp : 30.83	ASTM D751-19 (N)	
	weft : 28.84		
<b>Abrasion resistance :</b>	25 000	ISO 12947-2 (Cycles)	+/- 5%
<b>Others</b>	Certificate of compliance with the REACH regulation, confirming that the product meets the principles of the European Union directive REACH 1907/2006.		
<b>Laundry symbols :</b>	     DO NOT WASH   DO NOT BLEACH   DO NOT TUMBLE DRY   DO NOT IRON   DO NOT DRY CLEAN		
<b>Suitable method of treatment :</b>	Textile side of the fabric clean either dry with a soft brush or slightly wet cloth The fabric should be left to dry at room temperature		
<b>Recommended</b>	Recommended to store in a horizontal position, in a dry and well-ventilated area, away from sunlight and UV radiation		
In Drzovice 14.8.2024			

